

## Cisco TelePresence System 500

The Cisco TelePresence™ portfolio creates an immersive, face-to-face experience over the network—empowering you to collaborate with others like never before.

Through a powerful combination of technologies and design that allows you and remote participants to feel as if you are all in the same room, the Cisco TelePresence portfolio has the potential to provide great productivity benefits and transform your business. Many organizations are already using it to control costs, make decisions faster, improve customer intimacy, scale scarce resources, and speed products to market.

The Cisco TelePresence portfolio comprises a complete family of endpoints to meet many types of meeting needs:

- The Cisco TelePresence System 500 is designed for 1 or 2 users, bringing the Cisco TelePresence virtual in-person experience directly into the private office.
- The Cisco TelePresence System 1000 is for small group meetings and one-on-one conversations.
- The Cisco TelePresence System 1100 is designed for small group meetings and one-on-one conversations in multipurpose conference rooms.
- The Cisco TelePresence System 1300 Series is designed for group meetings in multipurpose conference rooms.
- The Cisco TelePresence System 3000 is for business meetings with up to 6 participants per room.
- The Cisco TelePresence System 3200 is for large group meetings of up to 18 participants per room.

These endpoints work with the complete Cisco TelePresence portfolio for easy call scheduling and setup; scalable, zero-latency multipoint calls; secure intercompany communications; and a host of compelling collaboration applications that scale a variety of meeting types, high-definition (HD) broadcasting, and industrial applications.

This data sheet discusses the Cisco TelePresence System 500 (Figure 1).

**Figure 1.** Cisco TelePresence System 500



## Product Overview

Cisco TelePresence systems combine life-like, ultra-high-definition video (1080p), quality audio, a specially designed environment, and interactive elements to create the feeling of being in person with meeting participants in remote locations. This simple, easy-to-use solution allows you and other participants to communicate naturally and effectively.

The Cisco TelePresence System 500 (part number CTS-500) brings the virtual in-person Cisco TelePresence experience directly into the private office. It allows individuals, subject matter experts, and executives to join Cisco TelePresence calls with equal stature—appearing life-size on Cisco TelePresence System 3000s and other endpoints.

The smaller footprint of the Cisco TelePresence System 500 can give your organization the flexibility to deploy this solution within personal offices to support intimate, remote one-on-one meetings or to join large, multipoint Cisco TelePresence calls. The Cisco TelePresence System 500 delivers the same award-winning video, audio, and environmental features that create the immersive, face-to-face experience consistent across the entire Cisco TelePresence portfolio.

## Applications

The Cisco TelePresence System 500 is ideal for joining large, multilocation group meetings, such as operational reviews, status update meetings, and quarterly customer presentations. It also supports personal meetings such as negotiations, job interviews, and personnel reviews.

The remarkable video clarity of the Cisco TelePresence System 500 allows you to see every expression, and the rich, CD-quality audio helps you hear every word. The ease of use and integrated, optimized features make it easy to schedule and launch calls by just pushing a button. Integration with the highly available Cisco network offers reliability, quality of service (QoS), and security, giving you the confidence to use it for both internal and external meetings.

## Features and Benefits

The Cisco TelePresence System 500 integrates transparently with the rest of the Cisco TelePresence portfolio to offer the same high-quality Cisco TelePresence experience, including:

- High-quality video at 720p and 1080p resolutions.
- Specially designed, high-definition cameras provide high-quality, high-definition images, with excellent eye contact and no user operation required.
- Full-duplex, CD-quality audio provides a rich audio experience with no perceivable latency and no interference from mobile devices or cell phones.
- Optimized lighting and audio quality.
- Multipoint meetings with up to 48 locations in any combination of Cisco TelePresence endpoints are possible.
- Integration with common enterprise calendaring programs offers easy and automated call start and controls—you just push a button.
- Impromptu meetings allow you to meet “in person” anywhere there is a Cisco TelePresence endpoint at a moment’s notice—with just a phone call.
- Integration with the network helps ensure reliability with high availability, security, and QoS for an optimal experience. Highly secure communications are enabled through encryption of both video and call signaling.
- The system offers any-to-any interoperability with standard- and high-definition video conferencing endpoints and collaboration with desktop video applications, such as Cisco WebEx™ meeting applications and the Cisco® Digital Media System.

- Secure and reliable intercompany and intracompany calls between your organization and any other, including with public Cisco TelePresence suites, is possible.

In addition to the overall benefits of the Cisco TelePresence design, the Cisco TelePresence System 500 offers the innovative features and benefits listed in Table 1.

**Table 1.** Cisco TelePresence System 500 Features and Benefits

Feature	Description	Benefits
<b>Optimized for one or two participants in a private office</b>	<ul style="list-style-type: none"> <li>• Offers elegant design with 37-in. display, camera, microphone, speakers, and lighting</li> <li>• Footprint is small</li> <li>• Available in three configurations: Free-standing pedestal, wall-mount, or table-top</li> </ul>	<ul style="list-style-type: none"> <li>• Offers sophisticated, discreet interface suited for private and executive offices</li> <li>• Allows you to sit 4 to 6 feet from the camera, a comfortable conversation distance in a typical office configuration</li> <li>• Offers flexible options to maximize room characteristics; easily installed with little or no room remediation or construction costs</li> </ul>
<b>Excellent audio and video quality</b>	<ul style="list-style-type: none"> <li>• Offers ability to project the Cisco TelePresence experience to any endpoint for large multipoint calls and intimate one-to-one meetings</li> <li>• Delivers the same quality virtual in-room experience as the rest of the Cisco TelePresence endpoint portfolio</li> <li>• Supports open microphone and speaker, with option for headset</li> </ul>	<ul style="list-style-type: none"> <li>• Individual Cisco TelePresence System 500 user appears life-size and of equal stature to other participants</li> <li>• Extends considerably the reach of the TelePresence experience across an organization at reasonable cost</li> <li>• Enables you to enjoy natural meeting environment, as well as headset for increased privacy</li> </ul>
<b>Connection for auxiliary graphics display*</b>	<ul style="list-style-type: none"> <li>• Allows you to show the data or graphics content on a separate auxiliary display or in presentation-in-picture mode</li> <li>• Can be used as a secondary PC monitor or video output for digital signage when not in a TelePresence call</li> </ul>	<ul style="list-style-type: none"> <li>• Offers flexible options for data display; presentation-in-picture mode suitable for space-constrained environments</li> <li>• Remains a useful productivity tool even when not involved in TelePresence calls</li> </ul>
<b>Lighting cues for optimal seating alignment</b>	<ul style="list-style-type: none"> <li>• Provides discreet positioning lights in the bezel that guide users to sit in the optimal camera location</li> </ul>	<ul style="list-style-type: none"> <li>• Frames the Cisco TelePresence System 500 user in best possible manner at other Cisco TelePresence endpoints</li> </ul>

\* Cisco does not provide graphics displays or mounts. Contact your Cisco TelePresence partner for data display options.

Table 2 lists the overall features and benefits of the Cisco TelePresence portfolio.

**Table 2.** Cisco TelePresence Portfolio Features and Benefits

Specification	Description
<b>Any-to-any interoperability support</b>	Cisco TelePresence systems can interoperate with standards-based H.323 video conferencing systems and other high-definition endpoints. In addition to protecting existing investments, interoperability dramatically expands the number of video conferencing endpoints that can communicate with a Cisco TelePresence system.
<b>Audio codec support</b>	G.711 and advanced audio coding with low delay (AAC-LD) audio compression codecs are available.
<b>Cisco TelePresence Auto Collaborate</b>	This Cisco innovation allows people in all rooms to instantly see and share information or objects with others by simply plugging in a device such as a laptop computer or the integrated optional high-definition document camera.  An optional presentation codec is dedicated to the data channel to provide full-motion (30-fps) graphics and multimedia content on the Cisco TelePresence Auto-Collaborate data channel.
<b>Cisco TelePresence Event Controls</b>	Through a web interface, event managers can control the flow of an event produced with a Cisco TelePresence system—providing a cost-effective way to reach wide audiences with spectacular and compelling results.
<b>Cisco TelePresence Expert on Demand support</b>	You can integrate Cisco TelePresence systems with Cisco Unified Communications and Cisco Unified Contact Center to deliver high-touch customer service and point-of-sale services.
<b>Cisco TelePresence Extended Reach</b>	An optimized 720p Cisco TelePresence mode provides wide-area bandwidth connections as low as 1.5-Mbps (T1/E1) speeds. The system maintains latency and packet loss while providing constrained bandwidth options for remote-office or telecommuter deployments.
<b>Cisco TelePresence Recording Studio</b>	Cisco TelePresence Recording Studio transforms Cisco TelePresence units into high-definition recording studios. Using an intuitive user interface on your existing Cisco TelePresence IP Phone, you can record high-quality video to deliver rich, immersive messages for internal and external communications, training, crisis management, etc. Viewing and distributing video content is easy; you can replay recordings on Cisco TelePresence endpoints or on standard browser-based players.

<b>Cisco TelePresence WebEx Engage</b>	Cisco TelePresence WebEx Engage extends Cisco TelePresence meetings to Cisco WebEx users. This solution offers unified scheduling and one-button-to-push meeting start, and it combines audio- and data-sharing capabilities. Remote attendees join through the Cisco WebEx Meeting Center and receive video from the Cisco TelePresence system. This integration improves user experience, making meetings easier and more productive.
<b>Configuration options</b>	You can statically configure IP address assignment or configure it through the Cisco TelePresence administrator web interface.
<b>Dialing buttons</b>	These buttons allow for convenient manual or address-book dialing.
<b>Directories</b>	Integration into the Cisco Unified Communications Manager general directory service provides a search function for thousands of directory entries.
<b>Document camera controls</b>	Software controls for the optional document camera have been incorporated into the Cisco TelePresence user interface on the Cisco IP Phone, providing for a more tightly integrated solution and more natural user controls. (This feature requires Cisco TelePresence Software Version 1.2 or later.)
<b>Encryption</b>	The Cisco TelePresence system supports full media and signaling encryption with no discernable latency to the Cisco TelePresence call for up to 48 segments. In addition, Cisco TelePresence meetings can be designated as nonsecure, secure best effort, and always secure. Meeting encryption status is indicated on-screen at the start of a call or when it changes, and on the phone at all times.
<b>Gigabit Ethernet switch</b>	The internal Cisco Gigabit Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network through an RJ-45 interface with single LAN connectivity for both the Cisco TelePresence system and a co-located Cisco Unified IP Phone 7975G and Ethernet-attached PC. The system administrator can designate separate VLANs (802.1Q) for the PC and Cisco IP Phones, providing improved security and reliability of voice and data traffic.
<b>Multipoint support</b>	Cisco TelePresence systems can participate in multipoint meetings by using the Cisco TelePresence Multipoint Switch.
<b>Mute and hold</b>	The Cisco TelePresence system supports mute and hold functions.  The mute feature has an on-screen mute indicator to alert participants that the mute feature was activated on the Cisco TelePresence microphone, causing all microphones to be simultaneously muted in remote rooms.  The Hold/Resume button toggles the video and audio mute features and allows you to place Cisco TelePresence systems on hold for privacy.
<b>Network-adaptive bandwidth usage</b>	The solution supports 720p or 1080p resolutions with three quality levels to optimize network bandwidth consumption. Cisco TelePresence systems can operate at several different bandwidth levels ranging from 2 to 5 Mbps for configurable, variable bandwidth consumption, maximizing the Cisco TelePresence experience while preserving frame rate and low latency and reducing packet loss. The solution is supported by all existing install, deployment, and operation services.
<b>Power over Ethernet (PoE) power for high-definition cameras and Cisco Unified IP Phone 7975G</b>	The Cisco high-definition cameras and Cisco Unified IP Phone 7975G receive power down the LAN from the Cisco IEEE 803.3af PoE switch incorporated into the Cisco TelePresence codec.
<b>Settings</b>	The web-based interface allows administrators to securely log in to the system to make configuration changes to the Cisco TelePresence systems.
<b>Signaling protocol support</b>	The Cisco TelePresence system supports Session Initiation Protocol (SIP) on Cisco Unified Communications Manager.
<b>Speed dial</b>	The Cisco TelePresence system allows up to 40 favorites entries for convenient speed dialing.
<b>System lighting</b>	The solution includes an integrated lighting assembly to eliminate facial shadows and provide natural-looking video without harsh studio lighting or makeup.  You can configure the integrated lighting assembly of the Cisco TelePresence system to turn on or off with a Cisco TelePresence call or with normal working hours. This feature reduces power consumption and provides a "greener" overall solution. (It requires Cisco TelePresence Software Version 1.4 or later.)
<b>U.S. Section 508 features</b>	The dial pad on the Cisco Unified IP Phone 7975G conforms to U.S. Section 508 guidelines. The 5-key dial pad has a raised nib that provides a tactilely discernible home key. To access more accessibility features, you can obtain the U.S. 508 Voluntary Product Accessibility Template (VPAT) at the following URL: <a href="http://www.cisco.com/go/accessibility">http://www.cisco.com/go/accessibility</a> .
<b>Volume control</b>	The convenient Volume Control button on the phone softkey menu provides for easy volume adjustments.

## Product Specifications

Tables 3 through 5 list specifications and Table 6 gives temperature ratings for the Cisco TelePresence System 500,.

**Table 3.** Product Specifications

Specification	Description
<b>Product compatibility</b>	<ul style="list-style-type: none"> <li>• Cisco TelePresence System 1000 with Cisco TelePresence System Software Version 1.4 or later</li> <li>• Cisco TelePresence System 1100 with Cisco TelePresence System Software 1.5 or later</li> <li>• Cisco TelePresence System 1300 Series with Cisco TelePresence System Software Version 1.5 or later</li> <li>• Cisco TelePresence System 3000 with Cisco TelePresence System Software Version 1.4 or later</li> <li>• Cisco TelePresence System 3200 with Cisco TelePresence System Software Version 1.4 or later</li> <li>• Cisco Unified Communications Manager 6.0 or later</li> <li>• Cisco TelePresence Multipoint Switch 1.0 or later</li> <li>• Cisco TelePresence Manager 1.4 or later</li> </ul>
<b>Software compatibility</b>	Cisco TelePresence System Software Version 1.4 or later
<b>Protocols</b>	Cisco Discovery Protocol, SIP, IP, Dynamic Host Configuration Protocol (DHCP), Secure Shell (SSH) Protocol, 802.1p/q, and Real-Time Transport Protocol (RTP)
<b>Connectivity</b>	Ethernet (1 LAN, RJ-45 connection: 100/1000m), internal 4-port Ethernet switch, and high-definition video connector
<b>Programming interfaces</b>	Web-based user interface; IP address assignment can be statically configured or configured through the Cisco TelePresence administrator web interface
<b>Physical dimensions (H x W x D)</b>	Minimum room dimensions: 8 x 6 x 8 ft (2.4 x 1.8 x 2.4m) Table top: 3 ft 0.5 in. x 3 ft 2 in. x 1 ft 4.5 in. (0.91 x 0.97 x 0.42m) Base width: 2 ft 7.5 in. (0.8m) Freestanding pedestal: Height: 5 ft 6.5 in. (1.7m); width: 3 ft 2 in. (0.97m) Base width: 2 ft 9 in. (0.84m); base depth: 2 ft 1 in. (0.64m) Wall-mounted pedestal: Height: 5 ft 6.5 in. (1.7m); width: 3 ft 2 in. (0.97m) Base width: 2 ft 9 in. (0.84m); base depth: 1 ft 1.5 in. (0.34m) Wall-mounted: Height: 2 ft 6 in. (0.76m); width: 3 ft 2 in. (0.97m)
<b>Weight</b>	<ul style="list-style-type: none"> <li>• 230 lb (104.3 kg) with pedestal</li> <li>• 65 lb (29.47 kg) without pedestal and codec</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>• 350W (3A @ 120V to 1.5A @ 240V)</li> <li>• Two power plugs are required</li> </ul>
<b>Total typical heat dissipation*</b>	<ul style="list-style-type: none"> <li>• 0.64kW</li> <li>• 1700 BTU/hr</li> </ul>

\*Typical accounts for a diversity of power consumption at 75 percent of maximum

**Table 4.** Video and Audio Specifications

Specification	Description
<b>Bandwidth consumption</b>	3 to 4 Mbps (1080p) or 1 to 3 Mbps (720p) for IP QoS connections is recommended. Note: The bandwidth recommendations for the Cisco TelePresence System 500 are identical to those for the Cisco TelePresence System 1000.
<b>Video standards</b>	H.264
<b>Video frame rate</b>	30 frames per second using H.264
<b>Data and graphics frame rate</b>	<ul style="list-style-type: none"> <li>• Graphics sharing at 5 frames per second (standard configuration)</li> <li>• Optional graphics sharing at 30 frames per second using a dedicated presentation codec</li> </ul>
<b>Native National Television Standards Committee (NTSC)</b>	720p and 1080p
<b>Resolution</b>	1920 x 1080 Native
<b>Audio standards</b>	G.711 and AAC-LD (22 kHz)
<b>Audio features</b>	Cisco Dynamic Echo Cancellation

<b>Cisco TelePresence HDC High-Definition Camera</b>	<ul style="list-style-type: none"> <li>• Complementary Metal Oxide Semiconductor (CMOS) 2/3-in. sensor</li> <li>• C-mount lens</li> <li>• 1080p 30</li> <li>• Minimum illumination 300 lux</li> <li>• Manual focus</li> </ul>
<b>H.264 interoperability</b>	Using Common Intermediate Format (CIF) and G.711 with Cisco Unified Videoconferencing 3500 Series platforms

**Table 5.** Additional Specifications

Specification	Description
<b>Firmware upgrades</b>	Downloadable from Cisco Unified Communications Manager
<b>Video network features</b>	Intelligent packet loss recovery of video transmission
<b>Network interface</b>	<ul style="list-style-type: none"> <li>• 1 LAN or Ethernet (RJ-45); 100/1000 Mbps</li> <li>• Internal 4-port Ethernet switch with 2 PoE (IEEE 802.3af) ports on codec</li> </ul>

**Table 6.** Temperature Ratings

Temperature	Description
<b>Office operating temperature</b>	Operating: 23 to 104°F (–5 to 40°C) Nonoperating: –13 to 158°F (–25 to 70°C)
<b>Relative humidity</b>	10 to 95% (noncondensing)

## Regulatory Compliance

- UL/CSA 60950
- IEC/EN 60950
- AS/NZS 60950
- 47CFR (Part 15) FCC Class B
- CISPR 22/ EN55022 Class B
- CISPR 24/EN55024

## Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#) and refer to Table 7.

**Table 7.** Ordering Information

Product Name	Part Number
<b>Cisco TelePresence System 500</b>	CTS-500
<b>Ordering Options for the Cisco TelePresence System 500</b>	
<b>Power cords</b>	Select the appropriate power cord pair option to plug into the wall outlets in the country where the Cisco TelePresence system will be deployed.
<b>Auxiliary control unit</b>	CTS-LIGHT-CTRL This is an optional control unit that is used to turn off system lighting when not in a meeting and is not required for Cisco TelePresence System 500 operation. The built-in lighting for the system is included and does not need to be ordered separately.
<b>Presentation codec</b>	CTS-HFR-COLLAB This chargeable option adds a dedicated presentation codec to enable high-frame-rate auto collaboration.

<b>Mounting Options</b>	<p><b>CTS500-STRUC-PED</b> This mounting option provides a free-standing floor mount for the Cisco TelePresence System 500 (CTS-500) with the codec integrated to the pedestal.</p> <p><b>CTS500-STRUC-TABL</b> This mounting option is for the display sitting on a table or shelf and the codec sits on the floor with a cable harness.</p> <p><b>CTS500-STRUC-WALL</b> This mounting option is for the display attached to a wall and the codec sits on the floor with a cable harness.</p>
-------------------------	--

## Service and Support

Cisco and our partners provide a broad portfolio of intelligent, personalized services and support that can help you realize the full value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation through a network-based collaboration platform that enables businesses to collaborate anywhere, anytime. For more information about these services, visit: [www.cisco.com/go/telepresenceservices](http://www.cisco.com/go/telepresenceservices).

## For More Information

For more information about the Cisco TelePresence System 500, please visit: <http://www.cisco.com/go/telepresence> or contact your local Cisco account representative or authorized Cisco partner.



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDR, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0910R)