




Systems Management



Monitoring, Diagnostics & Reporting



Personal Video Communications



Scheduling

TANDBERG Management Suite

One management platform for all your visual communication needs. TANDBERG Management Suite (TMS) provides complete visibility and control for on-site and remote video networks. It's scalable, easy-to-use and integrates with existing applications and third-party vendors to increase ROI.

The TANDBERG Management Suite is available as a software application or as a pre-installed server, enabling customers to choose a solution that best meets their network and scalability needs.



TMS Server

MANAGEMENT

- Complete management of on-site and remote video systems, including statistics, directories, booking and software updates
- Intuitive Web-based interface
- Manages network and video equipment from multiple vendors
- Manages calls made on multiple protocols (IP using H.323 and SIP, ISDN, V.35 and mixed calls)
- Manages endpoints, MCUs, network infrastructure, and gateways directly
- Supports automatic creation of phone books, including Active Directory and H.350
- Implements and manages automated software upgrades for video devices
- Easy mass configuration of systems

MONITORING/DIAGNOSTICS

- Detailed system and conference records
- Intelligent diagnostics enabling rapid response
- System summary page for fast access to most-used information
- Consolidated list of open tickets with links to recommended fixes
- Integrated Network Monitoring Support — Integrates with HP OpenView, IBM Tivoli®, NetCool® and any SNMP network monitoring tool
- Event notification prevents and minimizes negative service level

REPORTING

- Track all system usage and identify trends — packet loss, bandwidth usage, system auditing
- Call Detail Records and Statistics (CDRs)

SCHEDULING

- Scheduling or ad-hoc calling for video, audio, Web and data conferences
- Schedule conferences, book rooms and invite participants using Microsoft Outlook® or IBM Lotus Notes®*

* requires software option

TANDBERG EXPERTS SUPPORT TMS DEPLOYMENT AND TRAINING. GET THE MOST FROM YOUR INVESTMENT WITH PROFESSIONAL SERVICES. VISIT WWW.TANDBERG.COM

MANAGEMENT

CONFERENCE CONTROL CENTER

Complete conference overview on one screen
Conference and participant connection control
Conference-by-conference and system-by-system management and information

SYSTEM UPGRADES

Automatic download of new software and corresponding release keys

Release key import and export

SYSTEM CONTROL

Phonebook access
Monitoring and reporting
Software upgrades
Initiate, extend and terminate conferences
Change video layouts
Volume control and audio mute/unmute
Microphone on/off
Edit local phone books
Send messages to systems
Detect illegal system configurations
Gateway CDRs from MPS
REMOTE SYSTEM SUPPORT
Phone book access
Software Upgrades
Statistics

LANGUAGE

English (US)
Russian
French
Korean
Japanese
Chinese (Simplified)
Supports over 22 languages for booking and scheduling

INTELLIGENT TICKET HANDLING

Automated ticket handling (open/close)
Ticket priority customization
Proactive system check-up prior to engaging scheduled meetings
Intelligent Trouble Ticketing Handling
Diagnostic messages and solution suggestions
System status, gatekeeper status, SNMP configuration, ISDN/IP configuration and information

INTEGRATED NETWORK MONITORING SUPPORT

Integrates with HP OpenView, IBM Tivoli®, NetCool® and any SNMP network monitoring tool

TMS AGENT

Supports TMS Agent option for large scale provisioning of TANDBERG Movi and TANDBERG E20

PHONE BOOK SERVICES

Corporate directory enables multiple phone books and folders, browsing and searching from the endpoint
Supports server based TANDBERG, Polycom phone books, and H.350 white pages
Centrally-managed server phone books
Creation of one or multiple phone books
Search unlimited entries
Supports hierarchical phonebook structure for easy look-ups
Automatic directory import from gatekeeper, ILS and LDAP (single or multiple source)
Supports over 10 methods of automatic creation of phone books, including Active Directory and H.350
Create, edit, import and export phone books
Automatic application of national and international dialing rules
Automatic identification of ISDN/IP numbers
Automatic insertion of gateway (GW) prefix, area codes and country codes

ACCOUNT MANAGEMENT, SECURITY AND PERMISSIONS

FTP audit log from TANDBERG endpoints and MCUs
Flexibility to limit access to TMS features and limit access to endpoints
Definition and management of user profiles
Multiple security permissions
Single sign-on authentication of users using Windows® authentication

TEMPLATES/PROVISIONING

Customized template creation, management and distribution to systems
Selectable audio, video, network and bandwidth settings
Mass Deployment with automatic configuration from TMS
Ability to create persistent setting templates that can be proactively enforced on systems
Supports efficient and easy deployment of FindMe URI addresses to users

BACKUP

Capability to perform daily configuration restores, ensuring systems begin the day with the proper configuration
Backup system settings
Restore lost settings

MONITORING

GRAPHICAL MONITORING
Map monitor with graphic display
Customizable background images
Graphical display of call and system status

EVENT NOTIFICATION

Event Notification can be integrated into any SNMP Network Management system (e.g., HP Openview and IBM Tivoli)
E-mail notification to individuals or groups
Event logging including boot, link down/up, connect error, call connected/disconnected, lost response/got response, Downsampling, upgrade start/finish scheduling, gatekeeper registration, low battery, wrong password alert

BILLING INFORMATION

Flexibility to use billing and account codes
Full call detail records including billing or account codes for cost analysis or accounting

CALL DETAIL RECORDS (CDR) AND STATISTICS

Supports CDR capturing from Endpoints, MCUs, Gatekeepers and Gateways
Call detail records on screen or in native Excel format
Graphical display of call detail data
Support for multiple reporting formats: Onscreen, PDF or HTML
Number of incoming and outgoing calls
ROI Calculator
Call date and duration
Bandwidth usage
Network type
Number/address called
Statistics in data, graph and chart format
Number of scheduled conferences per person
Network, gatekeeper and ISDN interface
Authentication failure
Error statistics
Battery status

CALL ROUTING

Ability to support Best Impression Cascading and Least Cost Cascading
Automatic call routing on IP and ISDN
Least cost call routing on IP and ISDN
Automatic MCU, gateway and network selection
Supports MCU cascading, V.35, SIP, H.323, and H.320

SCHEDULING AND BOOKING*

SYSTEM BOOKING

Book system and meeting room simultaneously
Book recurring meetings and video resources
Create, password protect, edit or delete booked conferences
Add Web or data conference to meetings
Add/remove participants from reservation or connect/disconnect participants during conferences
Connect conferences ad-hoc or pre-schedule connection
Reserve resources for dial-in participants (telephone or video on ISDN or IP v.4 or IP v.6)
Schedule point-to-point conferences or bridged meetings
Lock conference, preventing new participants from joining
Invite participants by e-mail
Customize meeting names

SCHEDULE OVERVIEW

Overview of scheduled meetings, resources and participants
Real-time overview of meeting status

WEB AND DATA CONFERENCING

Integrated scheduling of WebEx conferences with video system booking
Create a data conference for participants to share applications and edit documents (Supports WebEx, Microsoft Live Meeting and TANDBERG See & Share)
An e-mail invitation is generated, enabling conference participants to link to the Web conference

INTEGRATION WITH MICROSOFT

EXCHANGE SERVER

Ability to schedule conferences, book rooms and invite participants using Microsoft Outlook
Requires Microsoft Exchange Server 2003 or 2007

INTEGRATION WITH IBM LOTUS DOMINO® SERVER

Ability to schedule conferences, book rooms and invite participants using IBM Lotus Notes and Lotus Sametime
Requires IBM Lotus Domino Server V6.x running on Microsoft Windows®

REDUNDANCY SUPPORT

Application Redundancy
Database Clustering

REQUIREMENTS

TMS SERVER (MINIMUM REQUIREMENTS)

1 GB RAM
Pentium 2 Ghz or higher Pentium compatible CPU
Microsoft Windows 2003 Server running the latest Service Packs with Internet Information Services, Microsoft Windows 2008 Server (32 bit) running the latest Service Packs with Internet Information Services, Microsoft .Net Framework version 3.5

TMS CLIENT REQUIREMENTS

Internet Explorer 6.0 or later, Firefox 2.0 or later, Java Virtual Machine Runtime Engine (JRE) 1.5.0 or later
SEE&SHARE SERVER REQUIREMENTS (IF INSTALLING SEE&SHARE OPTION)
Pentium I 500 MHz
Microsoft Windows 2003 Server or Microsoft Windows XP
256 MB RAM
20 MB of available disk space for services
SEE&SHARE CLIENT REQUIREMENTS
Internet Explorer 6.0 or higher

SOFTWARE OPTIONS

Microsoft Exchange Package
IBM Lotus Sametime Package
IBM Lotus Domino Package
3rd party booking API for customized integration
Network Integration Package (supports Cisco® IP/VC 3540, Polycom® MGC (Accord) MCU, RADVISION vialPC MCU and others)

* TMS includes TANDBERG Scheduler

All specifications subject to change without notice, system specifics may vary.

All images in these materials are for representational purposes only, actual products may differ.

TANDBERG is a registered trademark or trademark of TANDBERG in the U.S. and other countries.

All other trademarks are property of their respective owners.

TANDBERG MANAGEMENT SERVER

PROCESSOR & MEMORY

Intel® Pentium® 4 LGA775 CPU (Max. Intel® Pentium® 4 LGA775 CPU (Max. 3.6GHz with 800MHz FSB and 1MB Cache)
240-pin DIMM x 2, support Max. 2GB DDRII 400/533 memory

BIOS

Award System BIOS
Support Console redirection
Support Power on after power fail as the BIOS option
By-pass enable/disable as the BIOS option

PCI EXPANSION

On-board 32bit/33MHz Mini PCI Socket x1 (Master)

STORAGE

IDE 3.5" HDD x 1 (Stand Type) or IDE 3.5" HDD x 2 (Slim Type)
SATA 3.5" HDD x1 (Stand Type) or SATA 3.5" HDD x2 (Slim Type)
On-board Compact Flash Socket (Primary Channel)

COOLING SYSTEM

On-board 40 x 40 mm fan x 2
System 40 x 40 mm fan x 2 at Rear

ETHERNET

Marvell 8053 x 4 (PCI Express x 1); & #28; Copper (Base T, RJ45 with LED) GbE port x 4 (1, 2, 3, 4) & #28; LAN 1 & 2 support by-pass function

SYSTEM CONTROL AND INDICATOR

Power LED x 1 at Front
HDD Active LED x 1 at Front
AT Power Switch x 1 at Rear

SYSTEM I/O INTERFACE

COM port x 2 (Front x 1, Rear x 1)
USB 2.0 port x 4 (Front x 2, Rear x 2)
GPIO: 4 in 4 out
Optional 16 x 2 characters LCD Module with keypads through PIO Interface

ENVIRONMENTAL DATA

Operating temperature: 0°C to 40°C (32°F to 104°F)
Relative humidity: 10% to 90%
Storage and space in transport temperature: -20°C to 80°C (-4°F to 140°F) non-condensing

POWER

100-240 VAC, 50-60 Hz, 250W max

PHYSICAL DIMENSIONS

Height: 1.7" (44mm)
Width: 16.8" (426mm)
Depth: 16.4" (419mm)
19" rack-mountable,
1U height



TANDBERG

Management Suite

TANDBERG WORLD HEADQUARTERS

Philip Pedersens vei 20
1306 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 126 126
tandberg@tandberg.com

1212 Avenue of the Americas,
24th Floor
New York, NY USA 10036
Tel: +1 212 692 6500
Fax: +1 212 692 6501
Video: +1 212 692 6535
tandberg@tandberg.com

September 2009